

**KRITSNAM TECHNOLOGIES**  
SMPS Manufacturer

<b>Technical Data</b>		KRL-600-48
<b>Input Data</b>		
<b>AC-Input Voltage</b>		AC 380-500V
<b>DC-Input Voltage</b>		DC 540-710V
<b>EN61000-3-2(PFC-Norm)</b>		Not-fulfilled
<b>Harmonic Correction</b>		Passive
<b>Power Factor</b>		0.52
<b>Peak turn on current</b>		30A
<b>External Input Fuse Recommendation</b>		min. -6A
<b>Output Data</b>		
<b>Nominal Voltage</b>		48VDC
<b>Adjustment Range</b>		47.5-50V
<b>Output Current Range</b>		12A - 12.5A
<b>Output Current</b>		12 at 50V 12.5A at 48V
<b>Output Power</b>		600W
<b>Max. Ripple</b>		480mVpp
<b>Max Peak output current</b>		150% (capacitive load) for 300ms
<b>Overview</b>		
<b>Size (LxWxH)</b>		235mm x 125mm x 65mm
<b>Line &amp; Load Regulation</b>		<1%
<b>Efficiency, typ.</b>		85-89%
<b>Power Losses, typ.</b>		53W
<b>Protections</b>		-Short circuit-retry every 1.5sec -Input Transient 680VAC

Plot-591, GuruKrupa Industrial Society, Bhestan, Surat-395023.

Email: [kritsnamtechnologies@gmail.com](mailto:kritsnamtechnologies@gmail.com)

web: [www.kritsnamtechnologies.in](http://www.kritsnamtechnologies.in)

Mobile: +919099855172